Product Data Sheet



AC-25 Brake Fluid – Dot 4

45 Magnesium Street, Narangba QLD 4504 Phone: 07 3204 8511 | Fax: 07 3204 8522 www.auschem.com

High Performance Premium Grade Synthetic Brake Fluid Suitable for Disc and Drum Brake Systems in Automotive and Commercial Applications Including ABS

PRODUCT INFORMATION

AC-25 is a Premium Quality Polyglycol Synthetic Brake Fluid for use in Modern Brake Systems and is Ideal for Light and Commercial Vehicles with ABS Systems.

AC-25 Offers Superior Safety by Preventing Vapor Lock and Resists the Absorption of Water, Providing Highly Effective Corrosion Protection.

AC-25 Provides a High Temperature Resistant Formula with Increased Boiling Protection.

SPECIFICATIONS

AC-25 Meets the Following Specifications:				
AS 1960.1	HN 1796	SAE J 1704		
FMVSS 116 DOT 4	ISO 4925			

DIRECTIONS FOR USE

- 1. Flush Used Fluid from System.
- 2. Clean System Components to Remove Contaminants.
- 3. Add Fluid Following OEM Recommendations.
- 4. Reseal AC-25 Container Immediately to Prevent Contamination.

Note:

- Do Not Allow Contact with Paintwork
- Do Not Mix Brake Fluids
- Dispose Empty Containers According to Local Regulations

Product Data Sheet



AC-25 Brake Fluid - Dot 4

45 Magnesium Street, Narangba QLD 4504 Phone: 07 3204 8511 | Fax: 07 3204 8522 www.auschem.com

High Performance Premium Grade Synthetic Brake Fluid Suitable for Disc and Drum Brake Systems in Automotive and Commercial Applications Including ABS

TYPICAL PROPERTIES

Appearance	Green or Amber Liquid	
рН	7.0 - 8.0	
ER Boiling Point	243 – 265 °C	
Wet ERBP °C Min	155 ℃	
Solubility	Soluble	
DG Class	Non-Dangerous Good	
Hazardous	No	
Flash Point	>130 °C	
Reserve Alkalinity	40.0	







PRODUCT CODES / QUANTITIES

Available AC-25	Pack Size	Pack	Quantity
A/AC25/500	500ml	Bottle	Carton (12)
A/AC25/5	5L	Bottle	Carton (4)
A/AC25/20	20L	Cube	
A/AC25/200	200L	Drum	
A/AC25/1000	1000L	IBC	