

AC-26 Brake Fluid – Dot 3

High Performance Premium Grade Synthetic Brake Fluid Suitable for Brake and Clutch Systems in Automotive, Commercial, Mining, Agricultural and Heavy-Duty Applications

PRODUCT INFORMATION

AC-26 is a Premium Quality Non-Silicone, Non-Mineral, Fully Synthetic Brake Fluid for use in a Wide Range of Applications.

AC-26 Is Recommended for use in Brake and Clutch Systems Where DOT-3 Fluid is Specified.

APPLICATIONS

Automotive	Drilling	Mining
Agricultural	Earth Moving	Motorcycle
Construction	Light Commercial	On & Off Highway Transport

SPECIFICATIONS

AC-26 Meets the Following Specifications:

AS 1960-2005 Grade 1	ISO 4925 Class 3
FMVSS 116 DOT 3	SAE J 1704

DIRECTIONS FOR USE

1. Flush Used Fluid from System.
2. Clean System Components to Remove Contaminants.
3. Add Fluid Following OEM Recommendations.
4. Reseal AC-26 Container Immediately to Prevent Contamination.

Note:

- Do Not Allow Contact with Paintwork
- Do Not Mix Brake Fluids
- Dispose Empty Containers According to Local Regulations

AC-26 Brake Fluid – Dot 3

High Performance Premium Grade Synthetic Brake Fluid Suitable for Brake and Clutch Systems in Automotive, Commercial, Mining, Agricultural and Heavy-Duty Applications

TYPICAL PROPERTIES

Appearance	Amber Liquid
pH	7.5 - 8.5
ER Boiling Point	240 – 260 °C
Wet ERBP °C Min	150 °C
Solubility	Soluble
DG Class	Non-Dangerous Good
Hazardous	No
Flash Point	>137 °C
Reserve Alkalinity	52.0

Non DG



PRODUCT CODES / QUANTITIES

Available AC-26	Pack Size	Pack	Quantity
A/AC26/500	500ml	Bottle	Carton (12)
A/AC26/5	5L	Bottle	Carton (4)
A/AC26/20	20L	Cube	
A/AC26/200	200L	Drum	
A/AC26/1000	1000L	IBC	