Product Data Sheet



AC-43 WATER BASED DEGREASER

45 Magnesium Street, Narangba QLD 4504 Phone: 07 3204 8511 | Fax: 07 3204 8522 www.auschem.com

Australian Formulated and Manufactured High Performance Water Based Degreaser for Automotive Workshops, Heavy Industries, Transport, Mining and Oil & Gas Applications

This is a Solvent Free Degreaser – Does Not Contain Petroleum, Kerosene, Aromatics, Phenols, Hydrocarbons or Chlorinated Solvents

PRODUCT INFORMATION

AC-43 is a Highly Concentrated, Water Based Degreaser. Cuts Through Tough Grease and Grime with a Highly Effective Emulsifiers, Wetting Agents, and Surfactant Formula.

High Flash Point is Suitable for Parts Washers and Solvent Tanks where Flammable Liquids Cannot be Used.

AC-43 will not Damage Rubber, Plastic, Paintwork, or Metals when used as Recommended.

AC-43 Inhibits Corrosion of Ferrous Metals.

TYPICAL PROPERTIES

Appearance	Clear Red Liquid	
pH (Undiluted):	11.0 – 12.0	
Specific Gravity:	0.98 – 1.02	
Odour:	Sweet Odour	
Flammable:	No	
Hazardous:	Yes	
DG Class:	Non-Dangerous Goods	
Solubility:	Soluble	
Boiling Point:	80 - 150°C	

Product Data Sheet



AC-43 WATER BASED DEGREASER

45 Magnesium Street, Narangba QLD 4504 Phone: 07 3204 8511 | Fax: 07 3204 8522 www.auschem.com

Australian Formulated and Manufactured High Performance Water Based Degreaser for Automotive Workshops, Heavy Industries, Transport, Mining and Oil & Gas Applications

This is a Solvent Free Degreaser – Does Not Contain Petroleum, Kerosene, Aromatics, Phenols, Hydrocarbons or Chlorinated Solvents

DIRECTIONS FOR USE

Degreasing: Best Results are Achieved Using Spray Applicators. Austech 1L Pump-Up Sprayer is Recommended for use with AC-43.

Solvent Tanks: Allow Parts to Soak for 15 mins, Drain and Rinse with Water. Mild Steel Tank is Acceptable.

Parts Washers: Set up As Per Manufactures Instructions.

Concrete Cleaning: Apply to Concrete and alloy 2-3 Min to Soak in. Scrub then Rinse off with Water.

Recommended Dilution	
Light Soil	1:10
Medium Soil	1:4
Heavy Soil	Use Neat
Pressure Washer	1:100

IMPORTANT: When Cleaning Unprotected Magnesium, Magnesium Alloys, or Polished Aluminium it is Recommended to Wet the Surfaces with Water Before Applying the Diluted Mixture of Water and AC-43. Reduce Contact time and Concentration for these applications.

PRODUCT CODES / QUANTITIES

Available AC-43	Pack Size	Pack	Quantity
A/AC43/1	1L	Bottle	Carton (6)
A/AC43/5	5L	Bottle	Carton (4)
A/AC43/20	20L	Can	
A/AC43/200	200L	Drum	
A/AC43/1000	10001	IBC	