

AC-45 CAUSTIC DEGREASER

Australian Formulated and Manufactured Water Based Heavy Duty Caustic Degreaser for Automotive and Heavy-Duty Workshops, Industrial, Agricultural and Oil & Gas Applications

PRODUCT INFORMATION

AC-45 is a Highly Concentrated Water Based Degreaser Formulated with Surfactants, Wetting Agents, and a Caustic Solution. Providing a Stable and Highly Effective Degreaser for use Neat or as a Diluted Solution.

AC-45 Is slow Drying Allowing it to Penetrate Baked on Crusts, Ideal for use as a Pretreatment in Industrial Applications. Stains can be Pretreated Hours Before Cleaning to Allow the Product to penetrate deep into the Surface and Lift the Stains.

AC-45 Originated as a Product to Clean Garbage Trucks Before Repainting. It was Required to Soak Through Layers of Clay, Grease, Food Waste, Hydraulic Fluid and Oils.

AC-45 Will not Damage Wires, Cables, or Hoses in the Engine Bay, But May Mark Painted Surfaces.

DIRECTIONS FOR USE

Degreasing: Best Results are Achieved Using Spray Applicators. Austech 1L Pump-Up Sprayer is Recommended for use with AC-43.

Concrete Cleaning: Apply to Concrete and allow 2-3 Min to Soak in. Scrub then Rinse off with Water.

Recommended Dilution

Light Soil	1:10
Medium Soil	1:4
Heavy Soil	Use Neat
Pressure Washer	1:100

IMPORTANT: When Cleaning Unprotected Magnesium, Magnesium Alloys, or Polished Aluminium it is Recommended to Wet the Surfaces with Water Before Applying the Diluted Mixture of Water and AC-43. Reduce Contact time and Concentration for these applications.

AC-45 CAUSTIC DEGREASER

Australian Formulated and Manufactured Water Based Heavy Duty Caustic Degreaser for Automotive and Heavy-Duty Workshops, Industrial, Agricultural and Oil & Gas Applications

TYPICAL PROPERTIES

Appearance	Clear Yellow Liquid
pH (Undiluted):	12.0 – 12.5
Specific Gravity:	0.98 – 1.02
Odour:	Moderate Odour
Flammable:	No
Hazardous:	Yes
DG Class:	Class 8 Corrosive
Solubility:	Soluble
Boiling Point:	80 - 150°C



PRODUCT CODES / QUANTITIES

Available AC-45	Pack Size	Pack	Quantity
A/AC45/5	5L	Bottle	Carton (4)
A/AC45/20	20L	Drum	
A/AC45/200	200L	Drum	
A/AC45/1000	1000L	IBC	