Product Data Sheet



45 Magnesium Street, Narangba QLD 4504 Phone: 07 3204 8511 | Fax: 07 3204 8522 www.auschem.com

AC-60 PARTS WASH FLUID

Nonflammable, Low Evaporation Solvent for Use in Recirculating Parts Wash Machines

PRODUCT INFORMATION

AC-60 is for use in Parts Baths, Tubs and Parts Washing Machines where Proximity to Ignition Sources Requires the use of a Nonflammable yet Effective Solvent.

This Product has a Higher Flash Point than most other Parts Wash Fluids Available Meaning it will Evaporate at a Considerably Slower Rate than its Competitors.

AC-60 Contains Surfactant Soaps to Work Together with the Solvents and Provide Fast and Effective Removal of Grease and Grime from Parts Made from Steel, Alloys, Plastics, and Composite Material.

AC-60 Emulsifies Well and Breaks at a High Rate.

This Product is Used Across Many Industries Including Trucking, Automotive, Agriculture, General Industry, Mining, Defense and Has Also Been Exported to Many South Pacific Nations.

TYPICAL PROPERTIES

Appearance:	Clear Red Mobile Liquid	
Density:	0.83 kg/L	
Odour:	Mild Hydrocarbon	
Solubility:	Immiscible	
Flash Point:	>65°C	
Flammable:	No. Combustible Liquid	
DG Class:	Non-Dangerous Goods	
Hazardous:	Yes	
Boiling Point:	175-340°C	



Non DG

PRODUCT CODES / QUANTITIES

Available AC-60	Pack Size	Pack	Quantity
A/AC60/5	5L	Bottle	Carton (4)
A/AC60/20	20L	Can	
A/AC60/200	200L	Drum	
A/AC60/1000	1000L	IBC	