Product Data Sheet



AC-75 LUBEX

45 Magnesium Street, Narangba QLD 4504 Phone: 07 3204 8511 | Fax: 07 3204 8522 www.auschem.com

Versatile Multi-Purpose Lubricant and Penetrant Repels Moisture Providing Excellent Corrosion Protection on Metal Surfaces

PRODUCT INFORMATION

AC-75 is a Superior Quality Lubricant and Penetrant Designed for use by Engineering Trades People, Mechanics, Maintenance Personnel, in the Home or Workshop.

AC-75 Ensures Effective Penetration of Corroded Parts to Allow Easy Extraction, Ideal for Automotive, Industrial and Household Applications.

AC-75 Contains no Silicones or Hazardous Ingredients and Will Not Harm Plastics Or Rubbers.

APPLICATIONS

Automotive	Aviation
Electrical	Farming
Guns	Marine
Mining	Transport

DIRECTIONS FOR USE

- 1. Apply an Even Film of AC-75 on Metal Surfaces
- 2. Clean Off Excess AC075 with a Dry Cloth

TYPICAL PROPERTIES

Appearance:	Clear Amber Oil	
pH:	Not Applicable	
Specific Gravity:	0.92— 0.94 g/ml	
Odour:	Slight Odour	
Flammable:	No	
Boiling Point:	150 - 172 °C	
Solubility:	Immiscible In Water	
DG Class:	No (Liquid) / Class 2 Flammable Gas (Aerosol Can)	
Hazardous:	Yes	







PRODUCT CODES / QUANTITIES

Available AC-75	Pack Size	Pack	Quantity
A/AC75/400	400g	Aerosol	Carton (12)
A/AC75/5	5L	Bottle	Carton (4)
A/AC75/20	20L	Cube	
A/AC75/200	200L	Drum	
A/AC75/1000	1000L	IBC	