Product Data Sheet



45 Magnesium Street, Narangba QLD 4504 Phone: 07 3204 8511 | Fax: 07 3204 8522 www.auschem.com

NON DG

AC-25 BRAKE FLUID – DOT 4

Premium Grade DOT 4 Grade 3 Brake Fluid

AC-25 is high performance synthetic brake fluid suitable for disc or drum brake systems including ABS systems where DOT 3 or DOT 4 is specified.

PRODUCT INFORMATION

AC-25 is a high performance polyglycol synthetic brake fluid suitable for all Australian, European, Asian, Japanese & American vehicles which specify DOT 3 or DOT 4 grade Brake Fluid. Ideal for both passenger and commercial vehicles including ABS systems. The AC-25 Brake Fluid has high temperature resistance and low moisture absorption providing superior boiling point and high vapour lock temperature throughout its service life. It is available in green or amber colour.

Conforms to the following:

Australian Standard AS 1960.1 SAE J 1704 FMVSS 116 SAE J 1703 HN 1796 ISO 4925

DIRECTIONS FOR USE

- 1. Clean and flush system prior to refilling
- 2. Add fluid in accordance to vehicle manufacturer's recommendation.
- 3. Reseal container immediately after to avoid contamination and absorption of moisture.

IMPORTANT:

- * Do not allow contact with paintwork.
- * Do not mix brake fluids.
- * Dispose of empty containers properly. Do not use empty container for storing other fluids.
- * It is recommended that Brake Fluid is replaced every 24 months.

TYPICAL PROPERTIES

Appearance:	Green liquid (also available in amber)
Density at 20 °C:	g/cm3 @ 20°C 1.061—1.081
Kinematic Viscosity at -40 °C:	1800 max
Kinematic Viscosity at 40 °C:	1.5 min
Boiling Point (typical result):	260°C min
Wet Boiling Point:	155°C min
Water %w/w:	0.2

PRODUCT CODES / QUANTITIES

A/AC25/(500) | 500mL Hand Grenade (Carton of 12) A/AC25/5 | 5L Plastic Bottle (Carton of 4) A/AC25/20 | 20L Plastic Cube A/AC25/200 | 200L Metal Drum