

AC-28 Brake Fluid DOT 5.1

Premium Grade DOT 5.1 Brake Fluid

AC-28 is a premium quality brake fluid suitable for applications where manufacturers specify DOT 5.1 is required.

PRODUCT INFORMATION

AC-28 is a premium quality, full synthetic, non silicone, DOT 5.1 brake fluid designed for use in a wide range of brake and clutch applications.

AC-28 is recommended for re-fill or top-up of brake and clutch systems in passenger cars, 4WD's, motorcycles, light and heavy duty commercial vehicles, mining, construction and agricultural equipment that require a non petroleum based brake & clutch hydraulic fluid.

Conforms to the following:

- Australian Standard AS 1960.1-2005 Grade 3
- FMVSS 116 DOT 5.1
- ISO 4925 Class 3
- SAE J 1704

TYPICAL PROPERTIES

Appearance: Amber Liquid

pH: 7.5 - 8.5

Odour: Slight Odour

ER Boiling Point: 240°C - 260°C

Wet ERBP °C min. 150°C

Solubility: Soluble

DG Class: Non Dangerous Goods

Hazardous: Yes

Flash Point: 137°C

Reserve Alkalinity: 52.00

NON DG



AC-28 Brake Fluid DOT 5.1

Premium Grade DOT 5.1 Brake Fluid

AC-28 is a premium quality brake fluid suitable for applications where manufacturers specify DOT 5.1 is required.

DIRECTIONS FOR USE

1. Clean and flush system prior to refilling
2. Add fluid in accordance to vehicle manufacturer's recommendation.
3. Reseal container immediately after to avoid contamination and absorption of moisture.

IMPORTANT:

- Do not allow contact with paintwork.
- Do not mix brake fluids

Dispose of empty containers properly. Do not use empty container for storing other fluids.

PRODUCT CODES / QUANTITIES

A/AC28/(500) | 500mL Hand Grenade (Carton of 12)

A/AC28/5 | 5L Plastic Bottle (Carton of 4)

A/AC28/20 | 20L Plastic Cube

A/AC28/200 | 200L Metal Drum

A/AC28/IBC | 1000L IBC